

# Digital Hydrometer/Density Meter



eter features leakproof housing for operation in industrial and field applications including battery testing for utilities and telecoms, food & beverage testing, quality control, biotechnology and many more. Supported measuring units include: density, density at reference temperature, specific gravity (sg), Alcohol, API, °Baumé, °Brix and five programmable custom functions to ensure your measurement requirements.

### Advantages

- 99.999% Accurate, tests specific gravity and temperature simultaneously
- User-Friendly Compact, lightweight, and allows for one-hand measurement. Large LCD display screen with backlight.
- Robust Rugged, comes with protective carrying case. Sustains tough field environments with leakproof housing
- Wireless Communication Infrared data interface for data exchange with a PC and data export to a printer (data transfer accessories included).
- Stores up to 1,024 total measurement results including timestamp and sample ID.
- Automatic temperature compensation
- Reliable CE Compliant and One Year Warranty



### Technical Specifications

<b>Measurement Range:</b>	Density: 0.000 – 3.000 g/cm <sup>3</sup> Sample Temperature: *0 – 80 °C (32* – 176 °F) Viscosity: 0 – 1,000 mPa
<b>Accuracy:</b>	Density: 0.001 g/cm <sup>3</sup> Temperature: ±0.2 °C (±0.4 °F)
<b>Resolution:</b>	0.0001 g/cm <sup>3</sup>
<b>Repeatability:</b>	0.0005 g/cm <sup>3</sup>
<b>Minimum Sample Volume:</b>	2 mL
<b>Communication:</b>	IrDA Interface
<b>Display:</b>	Backlit LCD
<b>Internal Storage:</b>	1024 Results
<b>Operating Environment:</b>	10 – 50 °C (-15 – 122 °F)
<b>Power Requirements:</b>	(2) AA Batteries
<b>Dimensions:</b>	140 x 138 x 27 mm (5.5 x 5.4 x 1.0 in)
<b>Weight:</b>	368 g (13 oz)